

Caller id DTMF\FSK

Cli at intercom call

Cli at incoming call

Cli at out going call

Cli at auto call back

Cli at call transfer

ALARM(daily\repeat)

TO VIEW PORT ON CLI PHONE

DAY/NIGHT MODE-AUTO/MANUAL

GLOBAL MEMMORY

SELECTIVE TRUNK ACCESS

TRUNK GROUPING

TRUNK ACCESS(Linear\Rotational)

REDIAL

ACCEPTED&DENIED TABLE

CALL BACK

CALL FORWARD MULTI LEVEL

CALL PICK UP

BARGE IN/RAID

HOT LINE JN\EXT

CONFERENCE

DYNAMIC LOCK

FLEXIBLE NUMBERING

DOOR RELAY(OPTIONAL)

DO NOT DISTURB

EXECUTIVE RING  
REMOTE PROGRAMMING

TECH NICAL SPECIFICATION

Technology	Microcontroller based spc		
Trunk loop resistance	1199 ohm		
Cross talk	Better than 69 db		
Input power	220 volt ac 50 hz		
Power consumption	12 watt		
Extn volt	57 volt		
Configuration& model	208		
Trunk	2		
Extn	8		
Dimensions in cm	L	B	H
	232	185	50
Weight in kg	2		