

Caller id DTMF\FSK

Cli at intercom call

Cli at incoming call

Cli at out going call

Cli at auto call back

Cli at call transfer

ALARM

Redial

REMOTE ALARM

DAY/NIGHT MODE-MANUAL

GLOBAL MEMMORY

SELECTIVE TRUNK ACCESS

TRUNK ACCESS(LINEAR/ROTATIONAL)

ACCEPTED&DENIED TABLE

CALL BACK

CALL FORWARD MULTI LEVEL

CALL PICK UP

SELECTIVE CALL PICK UP

BARGE IN/RAID

HOT LINE JN\EXT

CONFERENCE

UN SUPERVISED CON FRENCE

RING BACK CUSTOMISED

DYNAMIC LOCK

FLEXIBLE NUMBERING

CLI BASED AUTO CALL ROUTING

EMERGENCY CALLING GROUP

HUNTING GROUP

BUSY HUNTING GROUP

EXTERNAL CALL FORWARDING

PAGING

DOOR RELAY(OPTIONAL)

VOICE DISA

DO NOT DISTURB

EXECUTIVE RING

HOTEL FEATURES

TO VIEW PORT NO ON CLI PHONE

TOHUNTING GROUP

BUSY HUNTING GROUP

EXTERNAL CALL FORWARDING

PAGING

DOOR RELAY(OPTIONAL)

VOICE DISA

DO NOT DISTURB

EXECUTIVE RING

HOTEL FEATURES

TO VIEW PORT NO ON CLI PHONE

TO VIEW DATE&TIME

BULK PROGRAMMING

REMOTE PROGRAMMING

BATTERY BACK UP (ADAPTOR WITH CHARGER 12 VOLT

TECHNICAL SPECIFICATION

Technology	Microcontroller based spc		
Trunk loop resistance	1199 ohm		
Cross talk	Better than 69 db		
Input power	220 volt ac 50 hz		
Power consumption	50 watt		
Extn voltage	53 volt		
Configuration & model	24P		
Trunk	1-4		
Extn	23-20		
Dimension in mm	L	B	H
	360	255	130
Weight in kg	7.2		